

## Terrafix 200R - Geotextile

Function: Filtration & Drainage.

Terrafix 200R is a needle-punched nonwoven geotextile made of 100% virgin polypropylene staple fibers, which are formed into a random network for dimensional stability. Terrafix 200R resists ultraviolet deterioration, rotting, biological degradation, naturally encountered alkalis and acids. Polypropylene is stable within the pH range of 2-13.

Types of applications for 200R are: Subdrains, French Drains, Foundation Drains, Trench Drains, Blanket Drains.

200R provides good lateral drainage and is suitable for a wide spectrum of soil permeabilities.

Property	ASTM Test Method	Value Metric Units
<b>Typical Geotextile Properties</b>		
• Grab Tensile Strength	D 4632	401 N
• Grab Elongation	D 4632	50%
• Tear Resistance	D 4533	170 N
• Puncture CBR	D 6241	1180 N
• Permittivity	D 4491	2.00 sec <sup>-1</sup>
• Water Flow	D 4491	6095 l/min/m <sup>2</sup>
• Apparent Opening Size	D 4751	0.300 mm
• U.V. Stability	D 4355	70% @ 500hrs

The information contained herein has been compiled by TAG Ltd. and is, to the best of our knowledge, true and accurate. This information is offered without warranty. Final determination of suitability for use contemplated is the sole responsibility of the user. This information is subject to change without notice. Terrafix is a registered trademark of Terrafix Geosynthetics Inc. Terrafix 04-2018.