SGU 180 STRATAGRID® PRODUCT DATA SHEET

StrataGrid is a flexible, high-performance line of geogrid products used in soil reinforcement and other civil engineering applications. These geogrids are constructed using high tenacity polyester yarns utilizing a complex knitting process and polymeric coating to provide superior engineering properties. StrataGrid is engineered to be mechanically and chemically durable, in both the harsh construction installation phase and in aggressive soil environments.

		UNIT	SGU 180
MECHANICAL PROPERTIES			
Ultimate Tensile Strength (ASTM D 6637)	MD	kN/m (lbs/ft)	180 (12,334)
Creep Reduction Factor (at 20°c, 114 years design life)	MD	RF _{CR}	1.44
Creep Limited Strength	MD	kN/m (lbs/ft)	125 (8,565)
Partial Factor - Installation Damage (ASTM D 5818) In sand/silt/clay		RF _{ID}	1.10
Partial Factor - Environmental Effects (GRI-GG7, GRI-GG8) Environment, 3 < pH < 9		RF _D	1.10
Long Term Design Strength (LTDS) *sand/silt/clay	MD	kN/m (lbs/ft)	103.3 (7,079)
PHYSICAL PROPERTIES			
Roll dimensions (width x length)		m (ft)	1.9 x 88 / 3.8 x 88 / 5.7 x 88* / 3.8 x 438.9 (6.25 x 288 / 12.5 x 288 / 18.75 x 288* / 12.5 x 1,440) *made to order
Roll Area		sy	200 / 400 / 600 / 2,000
MOLECULAR PROPERTIES		'	
Molecular weight (GRI GG8, ASTM D4603)		g/mol	min. 25,000
Carboxyl end group (CEG) (GRI GG7, ASTM D7409)		mmol/kg	max. 30

^{*} Values above reflect published ultimate values and are derived from Minimum Average Roll Values (MARV).

geogrid.com 1-800-680-7750



 $[\]ensuremath{^{*}}$ Certain custom roll widths and lengths available upon request