

PRODUCT COMPARISON

Terrafix® TBX3000 vs. Tensar® BX1200

The primary difference between these two products is the variation in machine direction (MD) strength and cross-machine direction (XMD) strength. Most geogrid applications require equal multi-directional strength in the geogrid; this is most important in road applications where a change of vehicular direction (curves and intersections) requires interlock of aggregate in both directions. This requirement essentially makes a geogrid only as strong as its weakest direction. A true biaxial geogrid supports the aggregate to provide 360° radial load distribution. It is also important to note that the test values for Tensile Strength at 2% strain is the most important value to consider; most roadway applications for geogrids require the product to perform at less than 2% strain.

Terrafix® TBX3000 is **THE** choice for true biaxial geogrid performance and long term reliability.

Property	Test Method	Unit	Terrafix® TBX3000		Tensar® BX1200	
			MD	XMD	MD	XMD
Tensile Strength @ 2%	ASTM D 6637	kN/m	12.0	12.0	6.0	9.0
Tensile Strength @ 5%	ASTM D 6637	kN/m	20.0	20.0	11.8	19.6
Ultimate Tensile Strength	ASTM D 6637	kN/m	30.0	30.0	19.2	28.8
Aperture Size	measured	mm	39	39	25	33
Junction Strength ¹	GRI-GG2	kN/m	27.9	27.9		
Junction Efficiency ¹	ASTM D 7737	%	93	93	93	93
Flexural Stiffness	ASTM D 7748	mg-cm	4,806,000	2,619,000	750,000	

Based on the above data, Terrafix® TBX3000 will perform as well as or better than Tensar® BX1200.



Isabel Perez
Product Manager, Geogrids

Notes:

1. Junction Efficiency is defined as the percentage of the product's Junction Strength as a function of its UTS. The test methods according to GRI-GG2 and ASTM D7737 (Meth. A) are essentially identical, other than a 1 degree C ambient temperature requirement.

The information contained herein has been compiled by *Terrafix Geosynthetics Inc.* and is, to the best of our knowledge, true and accurate at the time of compilation. The information provided is for reference purposes only and is not intended as a warranty or guarantee, implied or inferred. Terrafix Geosynthetics Inc. assumes no liability in connection with the use of this information.

16 October 2014