

Flexterra[®] HP-FGM[®] is a biodegradable, High Performance-Flexible Growth Medium (HP-FGM) composed of 100% recycled, Thermally Regined virgin wood fibres, crimped biodegradable interlocking fibres derived from regenerated cellulose sourced from sustainably harvested wood, micro-pore granules, naturally derived cross-linked biopolymers and water absorbents. The HP-FGM is patented, made in the US, plastic-free, and phytosanitized to eliminate potential weed seeds and pathogens. Flexterra[®] requires no curing period and upon application forms an intimate bond with the soil surface to create a continuous, porous, absorbent and flexible erosion resistant blanket that allows for rapid germination and accelerated plant growth.

Recommended Applications:

- Erosion control for slopes ranging from mild to severe ($\leq 0.25H:1V$)
- Rough graded slopes
- Superior performance compared to rolled erosion control blankets
- Enhancement of vegetation establishment
- Ideal infill material for Futerra[®] Turf Reinforcement Mats to create the GreenArmor[®] System

Technical Data			
Physical Properties*	Test Method	Units	Tested Value
Mass/Unit Area	ASTM D6566 ¹	g/m ² (oz/yd ²)	≥ 390 (11.6)
Thickness	ASTM 6525 ¹	mm (in)	≥ 5.6 (0.22)
Ground Cover	ASTM 6567 ¹	%	≥ 99
Water Holding Capacity	ASTM D7367	%	≥ 1,700
Material Colour	Observed	n/a	Green
Performance Properties*	Test Method	Units	Tested Value
Cover Factor ²	ASTM D8298-Type 1	n/a	≤ 0.01
Percent Effectiveness ³	ASTM D8298-Type 1	%	≥ 99
Vegetation Establishment	ASTM D7322	%	≥ 800
Functional Longevity ⁴	ASTM D5228	months	≤ 18
Cure Time	Observed	hours	0 - 2
Environmental Properties*	Test Method	Units	Tested Value
Ecotoxicity ⁵	EPA 2021.0	n/a	Non-Toxic
Biodegradability	ASTM D5338	n/a	Yes
USDA BioPreferred [®] BioBased Content	ASTM D6866	%	100
Elemental Impurity Limits	ASTM D8082	Pass/Fail	Pass
Carbon Footprint ⁶	Life Cycle Assessment	Unit CO ₂ e/Unit of product ⁷	≤.4
Product Composition			Typical Value
Thermally Processed Wood Fibres ⁸ (within a pressurized vessel)			80%
Wetting Agents-including high-viscosity colloidal polysaccharides, cross-linked biopolymers, and water absorbents			10 %
Crimped Biodegradable interlocking Fibres derived from regenerated cellulose sourced from sustainably harvested wood			5 %
Micro-Pore Granules			5%

* When uniformly applied at a rate of 3,500 pounds per acre (3900 kilograms/hectare) under laboratory conditions. 1. ASTM test methods developed for Rolled Erosion Control Products that have been modified to accommodate Hydraulic Erosion Control Products. 2. Cover Factor is calculated as soil loss ratio or treated surface versus an untreated control surface. 3. % Effectiveness - one minus Cover Factor multiplied by 100% 4. Functional Longevity is the estimated time period, based upon field observations, that a material can be anticipated to provide erosion control and agronomic benefits as influenced by composition, as well as site-specific conditions, including: but not limited to - temperature, moisture, light conditions, soils, biological activity, vegetative establishment and other environmental factors. 5. 48-hour LC₅₀ >100% - LC₅₀ refers to the percent concentration of a substance in water when 50% percent mortality of an organism is reached. 50% mortality of the tested species (*Daphnia magna*) could not be achieved when subjected to 100% effluent concentration proving the material to be acutely non-toxic. 6. Cradle to factory gate (Conover, NC) life cycle assessment. 7. "Carbon dioxide equivalent" or CO₂e is a term for describing different greenhouse gases in a common unit. For any quantity and type of greenhouse gas, CO₂e signifies the amount of CO₂ which would have the equivalent global warming impact. The unit of CO₂e per unit of product is consistent ratio based on mass, regardless of what unit mass is chosen. For instance, there is 0.4 kg of CO₂e per kg of product or 0.4 oz CO₂e per oz of product. 8. Heated to a temperature greater than 360 degrees Fahrenheit (193 degrees Celcius) for 5 minutes at a pressure greater than 50 psi (345 kPa) in order to be Thermally Refined™ / Processed and to achieve phytosanitation.

Packaging Data			
Properties	Test Method	Units	Nominal Value
Bag Weight	Scale	kg (lb)	22.7 (50)
Bags per Pallet	Observed	#	40
UV and weather-resistant plastic bags. Pallets are weather-proof stretch wrapped with UV resistant pallet cover.			

To the best of our knowledge, the information contained herein is accurate. However, Terrafix Geosynthetics Inc. cannot assume any liability whatsoever for the accuracy or completeness thereof. Final determination of the suitability of any information or material for the use contemplated, of its manner Terrafix Geosynthetics Inc. 2025.